

Arria 10 Product Table

	Product Line	GX 160 SX 160	GX 220 SX 220	GX 270 SX 270	GX 320 SX 320	GX 480 SX 480	GX 570 SX 570	GX 660 SX 660	GX 900	GX 1150	GT 900	GT 1150
Resources	Part number reference	10AX016 / 10AS016	10AX022 / 10AS022	10AX027 / 10AS027	10AX032 / 10AS032	10AX048 / 10AS048	10AX057 / 10AS057	10AX066 / 10AS066	10AX090	10AX115	10AT090	10AT115
	Logic elements (K)	160	220	270	320	480	570	660	900	1,150	900	1,150
	System logic elements (K)	210	288	354	419	629	747	865	1,180	1,506	1,180	1,506
	Adaptive logic modules (ALMs)	61,510	83,730	101,620	118,730	181,790	217,080	250,540	339,620	427,200	339,620	427,200
	Registers	246,040	334,920	406,480	474,920	727,160	868,320	1,002,160	1,358,480	1,708,800	1,358,480	1,708,800
	M20K memory blocks	440	588	750	891	1,438	1,800	2,133	2,423	2,713	2,423	2,713
	M20K memory (Mb)	9	11	15	17	28	35	42	47	53	47	53
	MLAB memory (Mb)	1.0	1.8	2.4	2.8	4.3	5.0	5.7	9.2	12.7	9.2	12.7
	Hardened single-precision floating-point multipliers/adders	156/156	191/191	830/830	985/985	1,368/1,368	1,523/1,523	1,688/1,688	1,518/1,518	1,518/1,518	1,518/1,518	1,518/1,518
	18 x 19 multipliers	312	382	1,660	1,970	2,736	3,046	3,376	3,036	3,036	3,036	3,036
	Peak fixed-point performance (GMACS) ¹	343	420	1,826	2,167	3,010	3,351	3,714	3,340	3,340	3,340	3,340
	Peak floating-point performance (GFLOPS)	140	172	747	887	1,231	1,371	1,519	1,366	1,366	1,366	1,366
Clocks, Maximum I/O Pins, and Architectural Features	Global clock networks	32	32	32	32	32	32	32	32	32	32	32
	Regional clocks	8	8	8	8	8	8	16	16	16	16	16
	Maximum LVDS channels (1.6 G)	120	120	168	168	222	324	270	384	384	312	312
	Maximum user I/O pins	288	288	384	384	492	696	696	768	768	624	624
	Transceiver count (17.4 Gbps)	12	12	24	24	36	48	48	96	96	72	72
	Transceiver count (25.78 Gbps)	–	–	–	–	–	–	–	–	–	6	6
	PCI Express® (PCIe®) hardened IP blocks (Gen3 x8)	1	1	2	2	2	2	2	4	4	4	4
	Maximum 3 V I/O pins	48	48	48	48	48	48	48	–	–	–	–
	Package Options ² and I/O Pins ³ : General-Purpose I/O (GPIO) Count, High-Voltage I/O Count, LVDS Pairs ⁴ , and Transceiver Count											
U19	U484 pin (19 mm)	192, 48, 72, 6	192, 48, 72, 6	–	–	–	–	–	–	–	–	–
F27	F672 pin (27 mm)	240, 48, 96, 12	240, 48, 96, 12	240, 48, 96, 12	240, 48, 96, 12	–	–	–	–	–	–	–
F29	F780 pin (29 mm)	288, 48, 120, 12	288, 48, 120, 12	360, 48, 156, 12	360, 48, 156, 12	360, 48, 156, 12	–	–	–	–	–	–
F34	F1152 pin (35 mm)	–	–	384, 48, 168, 24	384, 48, 168, 24	492, 48, 222, 24	492, 48, 222, 24	492, 48, 222, 24	504, 0, 252, 24	504, 0, 252, 24	–	–
F35	F1152 pin (35 mm)	–	–	384, 48, 168, 24	384, 48, 168, 24	396, 48, 174, 36	396, 48, 174, 36	396, 48, 174, 36	–	–	–	–
KF40	F1517 pin (40 mm)	–	–	–	–	–	696, 96, 324, 36	696, 96, 324, 36	–	–	–	–
NF40	F1517 pin (40 mm)	–	–	–	–	–	588, 48, 270, 48	588, 48, 270, 48	600, 0, 300, 48	600, 0, 300, 48	–	–
RF40	F1517 pin (40 mm)	–	–	–	–	–	–	–	342, 0, 154, 66	342, 0, 154, 66	–	–
NF45	F1932 pin (45 mm)	–	–	–	–	–	–	–	768, 0, 384, 48	768, 0, 384, 48	–	–
SF45	F1932 pin (45 mm)	–	–	–	–	–	–	–	624, 0, 312, 72	624, 0, 312, 72	624, 0, 312, 72	624, 0, 312, 72
UF45	F1932 pin (45 mm)	–	–	–	–	–	–	–	480, 0, 240, 96	480, 0, 240, 96	–	–

Notes:

- Fixed-point performance assumes the use of pre-adder.
- All packages are ball grid arrays with 1.0 mm pitch, except for U19 (U484), which is 0.8 mm pitch.
- A subset of pins for each package are used for 3.3 V and 2.5 V interfaces.
- Each LVDS pair can be configured as either a differential input or a differential output.
- Certain packages might not bond out all PCIe hard IP blocks.
- All data is correct at the time of printing, and may be subject to change without prior notice. For the latest information, please visit www.altera.com.

192, 48, 72, 6

Numbers indicate GPIO count, high-voltage I/O count, LVDS pairs, and transceiver count. Indicates pin migration.

Arria 10 SoC Hard Processor System

Product Line	SX 160	SX 220	SX 270	SX 320	SX 480	SX 570	SX 660
Part number reference	10AS016	10AS022	10AS027	10AS032	10AS048	10AS057	10AS066
Processor	Dual-core ARM® Cortex®-A9 MPCore™ processor						
Maximum processor frequency	1.5 GHz ¹						
Processor cache and co-processors	L1 instruction cache (32 KB) L1 data cache (32 KB) Level 2 cache (512 KB) shared FPU single and double precision ARM Neon™ media engine ARM CoreSight™ debug and trace technology Snoop control unit (SCU) Acceleration coherency port (ACP)						
Scratch pad RAM	256 KB						
HPS DDR memory	DDR4 and DDR3 (Up to 64 bit with ECC)						
DMA controller	8 channel						
EMAC	3X 10/100/1000 EMAC with integrated DMA						
USB OTG controller	2X USB OTG with integrated DMA						
UART controller	2X UART 16550 compatible						
SPI controller	4X SPI						
I²C controller	5X I²C						
Quad SPI flash controller	1X SIO, DIO, QIO SPI flash supported						
SD/SDIO/MMC controller	1X eMMC 4.5 with DMA and CE-ATA support						
NAND flash controller	1X ONFI 1.0 or later 8 and 16 bit support						
General-purpose timers	7X						
Software-programmable GPIOs	Maximum 54 GPIOs						
Direct shared I/Os	48 I/Os to connect HPS peripherals directly to I/O						
Watchdog timers	4X						
Security	Secure boot, AES, and secure hash algorithm						

Notes:

1. With overdrive feature.